

Edgewood

6000 S

Original post set 1820 by hendricks with witness: 18" sugar S 31 W 40 links, 10" beech N 11 W 14 links per Marion County Atlas pg. 9. 9-17-1851 Hosbrook set stone with witness: 10" sugar S 31 E 13 links, 15" beech N 15 W 50 links. 10-8-54 Cathcart called iron pipe. 5-11-55 Unversaw called iron pipe. 12-30-71 Wilcoxen called PK nail over iron pipe. 5-9-75 Fortner called same. 1-13-87 Gries called same. 2-20-90 Wilcoxen called same. 6-26-90 excavated PK nail found at surface. A 1/2" iron pipe found 3" down inside 2" lead pipe 30" long and 10" down from surface. No stone fd. Harrison set. Re-tied 4-17-95. Re-tied 4-24-00. Re-tied 4-1-05 by Wilcoxen. Re-tied 10-24-07 by Wilcoxen.

REF.	DISTANCE	DESCRIPTION	
1.	142.83'	Top center of corner fence post	
2.	39.34'	PK nail SW PwP#39-733 4"up	Mark of the Control o
3.	56.56'	Northeasterly corner of brick sign	
4.	58.54	Westerly corner of brick sign	
5.	124.85	NF corner of address #4455	
6.	171.42'	Mag nail S PwP#32-732 12"up	
7.	26.45	PK nail NF light pole	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			